



- Resistant to water, weather and UV
- High adhesive force in cold and heat
- Robust and tear resistant

**Delivery form**

	Box weight [kg]	Roll length [m]	Roll width [mm]	Box contents [units]
PAVATAPE 75	13.0	15	75	6
PAVATAPE 150	13.3	15	150	4

**Field of application**



**Technical data**

Material	Butyl rubber with aluminium carrier
Thickness [mm]	0.8
Minimum installation temperature for base and air [°C]	+5
only with PAVAPRIM [°C]	-10
Installation temperature Tape [°C]	+5 to +40
Temperature resistance [°C]	-40 to +100

**Product description**

For waterproof, weatherproof, UV-resistant sealing of board joints, connections and penetrations in PAVATEX insulation and sarking systems. When gluing to woodfibre boards or other porous or mineral contact surfaces, a preliminary coating of PAVABASE or PAVAPRIM is always applied.

You will find details on usage and installation guidelines in the sealing brochure.

**Storage**

Cool and dry, protected from sunshine.

Acara Concepts Ltd  
 Killossery  
 Kilsallaghan  
 Swords, Co Dublin, Ireland

Tel IRL: +353 (0)1 8409 286  
 Tel UK: +44 (0)20 7998 1690  
[www.acaraconcepts.com](http://www.acaraconcepts.com)  
[info@acaraconcepts.com](mailto:info@acaraconcepts.com)

**PAVATEX system guarantee**

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

