



PAVANATUR

- Render-compatible windowframe finishing
- Is applied in combination with ~~DIFFUTHERM / PAVADENTRO / PAVAWALL~~-products
ISOLAIR MULTI or PAVADRY
- Easy installation

Packaging

Thickness [mm]	Boards/pallet	Dimensions [mm]	m ² /pallet [m ²]	Mass/pallet [kg]	Thermal resistance (R _d) [m ² .K/W]
30	448	1100 x 600	97,7	454	0,65
40	412	1100 x 600	73,9	458	0,90
19	120	1100 x 600	79.2	327	0.44

Characteristics

Density [kg/m ³]	155
Thermal conductivity (λ _d) (EN 12667) [W/(m.K)]	0,043
Specific heat capacity (c) [J/(kg.K)]	2100
Water vapour diffusion resistance coefficient (μ) [-]	3
Reaction to fire (EN 13501-1)	E
Compressive strength at 10 % deformation [kPa]	100
Tensile strength perpendicular to faces [kPa]	15
Waste code according to The European Waste Catalogue (EWC)	030105; 170201
Edge profile	straight

Product description

REVEAL BOARD is a render-compatible natural and ecological, thermal insulation board based on wood fiber.

REVEAL BOARD is used as a render-compatible windowframe finish in combination with ~~DIFFUTHERM / PAVADENTRO / PAVAWALL~~-products. **ISOLAIR MULTI or PAVADRY**

The board can be applied both along in the interior as the exterior. Always consult the local regulations and installation guidelines as well as the manufacturer's recommended render systems.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements. For more information, please refer to the relevant safety data sheet.

Storage

Store on a flat surface, keep dry and protected from sunlight.



Acara Concepts Ltd
Killossery, Kilsallaghan,
Co Dublin K67 E7N3, Ireland
www.acaraconcepts.com
info@acaraconcepts.com
Tel IRL: +353 (0)1 8409 286
Tel UK: 020 7998 1690